

## CLAIM AMENDMENTS

1 (PREVIOUSLY AMENDED). A composite monitoring system comprising:  
a patient monitor including a sensor arranged to sense a physiological characteristic of a patient and a signal processor coupled to said sensor and adapted to process the signal from said sensor and an output member; and  
a defibrillator module adapted to be selectively coupled to said patient monitor, said defibrillator module including a pulse generator responsive to commands to generate therapeutic pulses for the patient, and a data generator arranged to generate indication signals indicative of an operation of said defibrillator module;  
said patient monitor and said defibrillator module cooperating when coupled to transfer said indication signal to said output member [whereby] wherein said output member generates output signals corresponding to one of said patient characteristic and said indication signals;  
wherein said patient monitor is operational without said defibrillator module.

2 (ORIGINAL). The system of claim 1 wherein said output member includes a display generating visual images.

3 (ORIGINAL). The system of claim 1 wherein said output member includes a printer adapted to print a hard copies.

4 (ORIGINAL). The system of claim 1 wherein said sensor comprises a cardiac sensor adapted to generate an external ECG and wherein said patient monitor is adapted to transmit said external ECG to said defibrillator module.

5 (ORIGINAL). The system of claim 1 wherein said sensor is adapted to sense at least one of the physiological parameters selected from the group consisting of blood pressure, arterial pulse oximetry (SpO<sub>2</sub>), carbon dioxide (CO<sub>2</sub>), respiration, and cardiac output.

6 (ORIGINAL). The system of claim 1 wherein said defibrillator module includes a defibrillator display.

7 (ORIGINAL). The system of claim 1 wherein said defibrillator module includes a selector arranged and constructed to allow an operator to generate operational parameters for said defibrillator module, said operational parameters defining a mode of operation for said defibrillator module.

8 (ORIGINAL). The system of claim 6 wherein said defibrillator module includes a defibrillator display arranged to provide information associated with the selection of said operational parameters.

9 (CURRENTLY AMENDED). A composite monitor/defibrillator unit module adapted to be coupled to a separate patient monitor comprising:

an external patient monitor;

a physiological sensor to sense the intrinsic cardiac activity of a patient and to generate a sensor signal indicative of said intrinsic cardiac activity;

a controller arranged to receive said sensor signal and to generate corresponding commands;

a pulse generator arranged to generate therapeutic pulses for the patient in

response to said commands;

an output member associated with said controller and adapted to generate output signals indicative of an operation of the defibrillator, said output signals being selected for transmittal to said external patient monitor for display;

wherein said physiological sensor, controller, pulse generator and output member are coupled electrically and mechanically to said external patient monitor ~~external patient monitoring unit~~ to form an integral system.

10(ORIGINAL). The module of claim 9 wherein controller includes an arrhythmia detector arranged to receive said sensor signal and to determine a cardiac condition of the patient that requires therapy.

11(PREVIOUSLY AMENDED). The module of claim 10 wherein said output member is adapted to receive a physiological parameter detected by said external patient monitor, and wherein said arrhythmia detector is adapted to receive said physiological parameter and to make a determination for delivering therapy to the patient based on said physiological parameter.

12 (ORIGINAL). The module of claim 9 wherein said output member is coupled to said pulse generator and is adapted to generate said output signals to indicate generation of pulses by said pulse generator for said patient monitor.

13 (ORIGINAL). The module of claim 9 wherein said controller is arranged to define a plurality of modes of operation including a fully automatic, an advisory, a manual, and a pacing modes.

an output member associated with said controller and adapted to generate output signals indicative of an operation of the defibrillator, said output signals being selected for transmittal to said patient monitor for display;

wherein said patient monitor is operational without said defibrillator module.

19 (ORIGINAL). The module of claim 18 further comprising a sensor adapted to sense said sensor signal.

20 (ORIGINAL). The module of claim 18 wherein said controller is adapted to receive said sensor signal from said external patient monitor.

21 (ORIGINAL). The module of claim 18 further comprising a physiological parameter detector that detects a physiological parameter, said controller being adapted to transmit said physiological parameter to said external patient monitor for display and processing.

22 (PREVIOUSLY AMENDED). The composite system of claim 1 wherein said defibrillator module is adapted to operate in one of an automatic, semiautomatic and manual modes.

23-26 CANCELLED.